THE BALDWIN LOCOMOTIVE WORKS.
ENGINEERING DEPARTMENT
PHILADELPHIA, PA


STANDARD DRAWING
SHEET 12-4A
DATE 10-30-36

WATER GAUGE & COLUMN

SUPERSEDING 1-15-35

APPROVED

B.L.W. STD. ARRANGEMENT-I.C.C. RECOMMENDATION.



WATER GAUGE & FITTINGS. WITHOUT COLUMN-R. OR L.				
TYPE	WATER GAUGE		FITTING-A	
	STYLE #1	STYLE #2	BK. HD. NOT LAGGED	BK. HD. LAGGED
IRONCLAD	2015	2017	11536	11512
REFLEX	2034	2036		

WATER GAUGE & FITTINGS. WITH COLUMN.				
TYPE	WATER GAUGE	WATER COLUMN	FITTING B	FITTING C
IRONCLAD	2016	2037	11539	11537
REFLEX	2035	2069		

NOTE 1:- LOCATION OF GAUGE COCKS, WATER GAUGE & COLUMN - SHEETS 12-3 & 12-3A

LOCATING ALL FIXTURES ON BACK HEAD, MAKE CERTAIN TO CLEAR THROTTLE LEVER AND OTHER FIXTURES.

DOMESTIC ENGINES - APPLY IRONCLAD TYPE GUARD. } UNLESS OTHERWISE SPECIFIED
FOREIGN ENGINES - APPLY NATHAN REFLEX TYPE "C", STEM 6" LONG. }

THREADS ON VALVES, COCKS & FITTINGS, SCREWED INTO BOILER, OR OTHER FITTINGS ATTACHED TO BOILER, MUST BE "V" FORM-12 THDS. PER 1", TAPER 1" IN 12", UNLESS OTHERWISE SPECIFIED.